

INDUSTRIAL WALL SHUTTERS



Available for VI and PFG series Fans, these all metal shutters can be air activated or motorised using the IWS 3197 electrical shutter operator.

Shutter frames are in heavy gauge steel with rigidly welded corners and finished with a tough powder coat finish.

Extruded aluminium shutter blades are attached with screws and durable bronze bushings to provide smooth operation without lubrication or maintenance.

MODEL NO.	SUIT FAN	OD	ID	DEPTH (mm)
IWS42	1070mm	1240 x 1240	1170 x 1170	102mm
IWS48	1200mm	1390 x 1390	1321 x 1321	102mm

WHOLE HOUSE FAN CEILING SHUTTERS

Select from two styles of air activated ceiling shutter to suit rafters or gang nail truss roofing systems.

The "No Cut Truss" shutter has a fixed central blade which covers the bottom cord of the truss running across the ceiling opening. Pivoting blades on either side are wind operated.



Standard Shutter for rafters



No Cut Truss Shutter for Trusses

STANDARD SHUTTER

Fan Diameter	INTERNAL		EXTERNAL		Fan Diameter	INTERNAL		EXTERNAL	
	Length	Width	Length	Width		Length	Width	Length	Width
760mm	761	761	813	813	760mm	762	838	813	889
915mm	915	839	965	889	915mm	762	1050	815	1095
1070mm	1168	864	1219	915	1070mm	907	1189	970	1245
1220mm	1422	915	1473	965	1070mm	907	1189	970	1245
All Shutters finished in white enamel					All shutters finished in white enamel				

NO CUT TRUSS SHUTTER

Optional Motorised Shutters. Heavy duty shutters designed to operate smoothly and quietly with the motorised opener.

The white polyester enamel finish blends with most ceilings. The aluminium blades have felted edges for effective sealing. Available in two sizes only to suit the 915mm and 1070mm diameter Whole House Fans. The shutter motor is activated from the fan control switch and can be interfaced with a fire control system if required.

MOTORISED SHUTTERS

MODEL NO.	OD	ID
ACP36	970 x 970	920 x 920
ACP42	1118 x 1118	1067 x 1067

